## This project shall comply with the following:

The California Fire (CFC) & Building (CBC) Code, 2016 edition, as adopted by the City of Cupertino Municipal Code (CMC) and California Code of Regulations (CCR).

## The scope of this project includes the following:

Tentative Tract Map to consider 2,500 condominium units for The Rise-SB35 Modification Project. The project file in ProjectDox contains Tentative Tract Map drawings.

## **Plans Status:**

Plans are **APPROVED**, subject to the following conditions.

## **Plan Review Comments:**

- 1. Review of this Developmental proposal is limited to acceptability of site access, water supply and may include specific additional requirements as they pertain to fire department operations, and shall not be construed as a substitute for formal plan review to determine compliance with adopted model codes. Prior to performing any work, the applicant shall make application to, and receive from, the Building Department all applicable construction permits.
- 2. Traffic signal pre-emption shall be provided as deemed necessary by, and in coordination with, Santa Clara County Fire Department.
- 3. Buildings and Facilities Access: Approved fire apparatus access roads shall be provided for every facility, building or portion of a building hereafter constructed or moved into or with the jurisdiction. The fire apparatus access road shall comply with the requirements of this section and shall extend to within 150 feet of all portions of the facility and all portions of the exterior walls of the first story of the building as measured by an approved route around the exterior of the building or facility. [CFC, Section 503.1.1]. Dead-end fire access roads in excess of 150 feet in length, without an approved turnaround, shall include physical barriers to prevent fire apparatus traveling beyond 150 feet. Details of such means shall be subject to review and approval at time of building permit review.

City	PLANS	S SPECS NEW RMDL AS		s oc	CCUPANCY	CONST. TYPE		ApplicantName			DATE	PAGE				
CUP	$\boxtimes$					]   1	Mixed		I-A	Sandis		dis	6/3/2022	1	OF	
SEC/FLOOR	AREA LOAD PROJE						CT DESCRIPT	ION				I	PROJECT TYPE OR SYSTEM			
Site	Comm						mercial Development						Tentative Map			
NAME OF PROJECT									LOCATION							
THE RIS	ENTA	ATIV	'E MA	ıΡ				10123	N. W	olfe Rd C	upe	ertino				
TABULAR FIRE FLOW 6,000 REDUCTION FOR F									IRE SPRINKLERS REQUIRED FIRE FI			FLO				
									0%			,	3,000	Camp	bell, Ro	b 

4. Required Aerial Apparatus Access:

Case Manager

- a. Where required: Buildings or portions of buildings or facilities exceeding 30 feet (9144 mm) in height above the lowest level of fire department vehicle access shall be provided with approved fire apparatus access roads capable of accommodating fire department aerial apparatus. Overhead utility and power lines shall not be located within the aerial fire apparatus access roadway.
- b. Width: Fire apparatus access roads shall have a minimum unobstructed width of 26 feet (7925) in the immediate vicinity of any building or portion of building more than 30 feet (9144 mm) in height.
- c. Proximity to building: At least one of the required access routes meeting this condition shall be located within a minimum of 15 feet (4572) and a maximum of 30 feet (9144mm) from the building, and shall be positioned parallel to one entire side of the building, as approved by the fire code official. SCCFD SD&S A-1.
- 5. Turn Radius (circulating): The minimum outside turning radius is 42 feet for required access roadways. Greater radius up to 60 feet may be required where the Fire Department determines that Ladder Truck access is required. Circulating refers to travel along a roadway without dead ends.
- 6. Fire Hydrant Systems Required: Where a portion of the facility or building hereafter constructed or moved into or within the jurisdiction is more than 400 feet from a hydrant on a fire apparatus access road, as measured by an approved route around the exterior of the facility or building, onsite fire hydrants and mains shall be provided where required by the fire code official. [CFC, Section 507.5.1].
- 7. Timing of installation: When fire apparatus access roads or a water supply for fire protection is required to be installed, such protection shall be installed and made serviceable prior to and during the time of construction except when approved alternative methods of protection are provided. Temporary street signs shall be installed at each street intersection when construction of new roadways allows passage by vehicles in accordance with Section 505.2. Construction documents. Construction documents for proposed fire apparatus access, location of fire lanes, security gates across fire apparatus access and construction documents and hydraulic calculations for fire hydrant systems shall be submitted to the fire department for review and approval prior to construction. CFC Sec. 501.3, 501.4.

This review shall not be construed to be an approval of a violation of the provisions of the California Fire Code or of other laws or regulations of the jurisdiction. A permit presuming to give authority to violate or cancel the provisions of the fire code or other such laws or regulations shall not be valid. Any addition to or alteration of approved construction documents

City	PLANS	SPECS	NEW	RMDL	A	s oc	CUPANCY	CONS	ST. TYPE	Applica	ntName		DATE	PAGE	
CUP	$\boxtimes$					ו   נ	Mixed		I-A	Sar		ndis	6/3/2022	c	DF
SEC/FLOOR	AREA LOAD PROJECT DES							ION				PROJECT TYPE OR SYSTEM			
Site	Comn						nmercial Development					Tentative Map			
NAME OF PR		·						LOCATION							
THE RIS	ENTA	ATIV	'E MA	Р				10123	N. W	olfe Rd Cu	pertino				
TABULAR FIRE FLOW REDUCTION FOR F									IRE SPRINKLE	RS	REQUIRED FIRE F	LOW @ 20 PSI	BY		
	6,00	00					5	0%			3,000	Campl	bell, Ro	b	